


PICOBOX ref. 00900102



12V-24V

Trucks, Hunting, Fishing, Shelters



TECHNICAL DATA

Battery

- Lithium-polymer, LiFePo4
- Capacity : 9 Ah - 102 Wh
- Output Voltage : 12,8V (14.6V max)
- Output current : 80 A
- Current peak : 140 A
- Life time : min 3000 cycles DoD 70%
- Loading options : grid, vehicle, solar panel
- Grid max input current : 1 A
- Véhicule max input current : 5 A
- Solar panel max input current : 5 A
- Solar charge controller: MPPT

Solar panel

- Product type : P3-30 foldable panel
- System voltage rating : 12 V
- Rated power : 30 Wc
- Rated voltage at MPP : 22 V
- Rated current : 1.6 A
- Dimensions folded : 257 x 216 x 30.5 mm
- Dimensions unfolded : 1130 x 546 x 2.5 mm
- Weight : 0.83 kg

Connectors

Inputs

- AC 220V IEC
- 12V DC from vehicle
- 2 x MC4 solar connectors

Outputs

- 2 x 12V DC - Car cigarette lighter - max 20A
- 1 x USB - max 1A

Panel control

- Dynamic battery panel control

Protections

- Overcharging control
- Excessive discharging control
- Short-cut auto switch
- Over heat protection system
- Temperature range : -10 °C to 50 °C

Case

- Case type : Peli Storm Case
- Dimensions : 48.7 x 38.6 x 17 cm
- Total weight without PV : 5.5 kg
- Standards : ATA 300, MIL


2 years full warranty. 5 years battery and BMS

Information and terms above are not binding. ILAND reserves the right to change these terms at any time and at its sole discretion.

Contact

YURTE PANNELLI SOLARI
Cosimino Tumolo
Ch. du Sonnenberg 4
1700 Fribourg / Switzerland
www.yurte-pannelli-solari.com

Phone : +41 76 320 27 39
contatto@yurte-pannelli-solari.com



ILAND®

We make solar energy portable.
Wherever you are you have light, energy
and potable water.